


# Product data sheet

WANDLEUCHTE ARINI LIGHT+ 4000K  
17.10100.1VXXX + 17.81100.1V001  
HESS




Luminaire head and shield plate made of die-cast aluminium. Luminaire cover made of PMMA. Adjustment of the luminaire head in 10° increments, horizontal max. 120° and vertical max. 130°. Adjustment of the shield plate by 360° possible. Wall bracket ARINI For versions: Light, Light + (DALI), Light + (CASAMBI), Speaker, HiFi-Speaker Made of galvaniset steel Length: 206 mm Mounting plate dimensions: H200mm x B160mm Mounting material for wall fixation on site A connector for cable cross sections of 0,5 up to 1,5mm² is enclosed for connection of luminaire head


## Light output 1




1 x LED			
Nominal lamp power	54 W	LOR	100%
Lamp flux	4679 lm	ULOR	50%
Luminous efficacy	87 lm/W	Total flux	4679 lm
CCT	4000 K	Total power	54 W
CRI	80		



1 x LED			
Nominal lamp power	54 W	LOR	100%
Lamp flux	4551 lm	ULOR	50%
Luminous efficacy	84 lm/W	Total flux	4551 lm
CCT	4000 K	Total power	54 W
CRI	80		




1 x LED			
Nominal lamp power	54 W	LOR	100%
Lamp flux	5292 lm	ULOR	50%
Luminous efficacy	98 lm/W	Total flux	5292 lm
CCT	4000 K	Total power	54 W
CRI	80		



**1 x LED**

Nominal lamp power	54 W	LOR	100%
Lamp flux	5132 lm	ULOR	50%
Luminous efficacy	95 lm/W	Total flux	5132 lm
CCT	4000 K	Total power	54 W
CRI	80		



**1 x LED**

Nominal lamp power	54 W	LOR	100%
Lamp flux	5674 lm	ULOR	50%
Luminous efficacy	105 lm/W	Total flux	5674 lm
CCT	4000 K	Total power	54 W
CRI	80		

**Mounting mode**

Wall mounted, Pole integrated

**Shape and measurements**

Length: 8.83 in

Width: 6.30 in

Height: 7.87 in

**Adjustability**

Rotatable, Tilttable

**Electric**

System power: 54 W

**Protection**

IP: 66