

Product data sheet

POLE MOUNTED LUMINAIRE OSLO 650-2 - WITH LOUVERS 4000K

10.12430.0VXXX


HESS



IP 54


Round luminaire canopy, horizontally split in two, made of aluminium, plain coloured. Support elements made of aluminium, painted. Cylindrical luminaire enclosure made of PMMA. Round luminaire body made of aluminium, optionally with or without louvers.

Light output 1




1 x LED

Nominal lamp power	15 W	LOR	100%
Lamp flux	1406 lm	ULOR	100%
Luminous efficacy	94 lm/W	Total flux	1406 lm
CCT	4000 K	Total power	15 W
CRI	80		




1 x LED

Nominal lamp power	20 W	LOR	100%
Lamp flux	2010 lm	ULOR	100%
Luminous efficacy	100 lm/W	Total flux	2010 lm
CCT	4000 K	Total power	20 W
CRI	80		




1 x LED

Nominal lamp power	20 W	LOR	100%
Lamp flux	2235 lm	ULOR	100%
Luminous efficacy	112 lm/W	Total flux	2235 lm
CCT	4000 K	Total power	20 W
CRI	80		




1 x LED

Nominal lamp power	20 W	LOR	100%
Lamp flux	2122 lm	ULOR	100%
Luminous efficacy	106 lm/W	Total flux	2122 lm
CCT	4000 K	Total power	20 W
CRI	80		




1 x LED

Nominal lamp power	20 W	LOR	100%
Lamp flux	2089 lm	ULOR	100%
Luminous efficacy	104 lm/W	Total flux	2089 lm
CCT	4000 K	Total power	20 W
CRI	80		




1 x LED

Nominal lamp power	28 W	LOR	100%
Lamp flux	2686 lm	ULOR	100%
Luminous efficacy	96 lm/W	Total flux	2686 lm
CCT	4000 K	Total power	28 W
CRI	80		




1 x LED

Nominal lamp power	28 W	LOR	100%
Lamp flux	3013 lm	ULOR	100%
Luminous efficacy	108 lm/W	Total flux	3013 lm
CCT	4000 K	Total power	28 W
CRI	80		




1 x LED

Nominal lamp power	28 W	LOR	100%
Lamp flux	2672 lm	ULOR	100%
Luminous efficacy	95 lm/W	Total flux	2672 lm
CCT	4000 K	Total power	28 W
CRI	80		




1 x LED

Nominal lamp power	28 W	LOR	100%
Lamp flux	2973 lm	ULOR	100%
Luminous efficacy	106 lm/W	Total flux	2973 lm
CCT	4000 K	Total power	28 W
CRI	80		




1 x LED

Nominal lamp power	15 W	LOR	100%
Lamp flux	1486 lm	ULOR	100%
Luminous efficacy	99 lm/W	Total flux	1486 lm
CCT	4000 K	Total power	15 W
CRI	80		




1 x LED

Nominal lamp power	28 W	LOR	100%
Lamp flux	2778 lm	ULOR	100%
Luminous efficacy	99 lm/W	Total flux	2778 lm
CCT	4000 K	Total power	28 W
CRI	80		




1 x LED

Nominal lamp power	15 W	LOR	100%
Lamp flux	1564 lm	ULOR	100%
Luminous efficacy	104 lm/W	Total flux	1564 lm
CCT	4000 K	Total power	15 W
CRI	80		




1 x LED

Nominal lamp power	28 W	LOR	100%
Lamp flux	2823 lm	ULOR	100%
Luminous efficacy	101 lm/W	Total flux	2823 lm
CCT	4000 K	Total power	28 W
CRI	80		




1 x LED

Nominal lamp power	15 W	LOR	100%
Lamp flux	1462 lm	ULOR	100%
Luminous efficacy	97 lm/W	Total flux	1462 lm
CCT	4000 K	Total power	15 W
CRI	80		




1 x LED

Nominal lamp power	15 W	LOR	100%
Lamp flux	1414 lm	ULOR	100%
Luminous efficacy	94 lm/W	Total flux	1414 lm
CCT	4000 K	Total power	15 W
CRI	80		




1 x LED

Nominal lamp power	15 W	LOR	100%
Lamp flux	1626 lm	ULOR	100%
Luminous efficacy	108 lm/W	Total flux	1626 lm
CCT	4000 K	Total power	15 W
CRI	80		



1 x LED

Nominal lamp power	20 W	LOR	100%
Lamp flux	2162 lm	ULOR	100%
Luminous efficacy	108 lm/W	Total flux	2162 lm
CCT	4000 K	Total power	20 W
CRI	80		



1 x LED

Nominal lamp power	20 W	LOR	100%
Lamp flux	2020 lm	ULOR	100%
Luminous efficacy	101 lm/W	Total flux	2020 lm
CCT	4000 K	Total power	20 W
CRI	80		

Mounting mode

Pole top mounted

Shape and measurements

Length: 25.59 in

Width: 25.59 in

Height: 19.33 in

Electric

System power: 15-28 W

Protection

IP: 54

Adjustability

Fixed