


Product data sheet

RINQ PDI 1500 HÄNGELEUCHTE 193W 4000K CHAMPAGNER MATT PMMA OPAL
445-9215014130V1
MOLTO LUCE




RINQ HÄNGELEUCHTE aus Aluminium, champagner matt,satinierter PMMA Opaldiffuser Lichtaustritt direkt/- indirekt, mit Betriebsgerät, Kabel transparent, Pendellänge 4000mm IP20

Light output 1 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	24 W	CRI	80
Total flux	2482 lm	LOR	100%
Luminous efficacy	103 lm/W	ULOR	32%
		Total power	24 W

Light output 2 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	24 W	CRI	80
Total flux	2482 lm	LOR	100%
Luminous efficacy	103 lm/W	ULOR	32%
		Total power	24 W

Light output 3 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	24 W	CRI	80
Total flux	2482 lm	LOR	100%
Luminous efficacy	103 lm/W	ULOR	32%
		Total power	24 W

Light output 4 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	24 W	CRI	80
Total flux	2482 lm	LOR	100%
Luminous efficacy	103 lm/W	ULOR	32%
		Total power	24 W

Light output 5 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	24 W	CRI	80
Total flux	2482 lm	LOR	100%
Luminous efficacy	103 lm/W	ULOR	32%
		Total power	24 W

Light output 6 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	24 W	CRI	80
Total flux	2482 lm	LOR	100%
Luminous efficacy	103 lm/W	ULOR	32%
		Total power	24 W

Light output 7 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	24 W	CRI	80
Total flux	2482 lm	LOR	100%
Luminous efficacy	103 lm/W	ULOR	32%
		Total power	24 W

Light output 8 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	24 W	CRI	80
Total flux	2482 lm	LOR	100%
Luminous efficacy	103 lm/W	ULOR	32%
		Total power	24 W

Mounting mode

Pendant

Shape and measurements

Length: 59.05 in

Width: 59.06 in

Height: 3.94 in

Adjustability

Rotatable, Tilttable

Electric

System power: 192 W

Appliance Class: I

Protection

IP: 20

IK: 02