Product data sheet

LUMINAIRE CURVED PART COBRA CURVE 12.9W CRI > 80 4000K DALI
2010.6675 - COBRA LGT PLAN CURVED PART-900-120 BK 840 PA
REGENT



IP 20 IK 06

Luminaire curved part Cobra with LED, system power: 12.9 W, standby power 0.5 W, luminous flux of luminaire 900 lm, colour rendering index CRI > 80, colour temperature 4000 K, neutral white, colour tolerances SDCM 3, lifetime LED L80 50'000 h, photobiological safety: the luminaire poses no danger (RG0), 230 V, direct-indirect light emission, cover in PMMA, black, -M (matt), diffuser in polymethyl methacrylate (PMMA) wide beam, 1 integral control gear, DALI2, protection class II, ingress protection IP20, glow wire test 650 °C, impact strength: IK 06, L = 900 mm, B = 120 mm, H = 60 mm

Light output 1



1 x LED

Nominal lamp power	12.3 W	LOR	100%
Lamp flux	900 lm	ULOR	50%
Luminous efficacy	73 lm/W	Total flux	898 lm
CCT	4000 K	Total power	12.9 W
CRI	80		

Mounting mode

Wall mounted

Shape and measurements

Length: 0.04 in
Width: 0.04 in
Height: 0.04 in

Adjustability

Fixed

Design

Color of housing: Black

Electric

System power: 12.9 W
Appliance Class: II

Protection

IP: 20
IK: 06