
Product data sheet


LADOR 53 SURFACE FACADE LUMINAIRES
LD-30071-W-30
LIGMAN



IP 65 IK 08


- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K and 4000K - Die-cast aluminium housing - Pre-treated before powder coating ensuring high corrosion resistance - Thermal heat dissipation body - Single cable entry, through wiring upon request - One cable gland supplied with 0.2 m of 3x1.0 sqmm outdoor cable for LD-30001, LD-30011, LD-30021, LD-30031 - One cable gland supplied with 0.2 m of 8x0.5 sqmm outdoor cable for LD-30041, LD-30051,LD-30061, LD-30071 - Stainless steel fasteners in grade 304 with zinc flake coating (ZFC) - Durable silicone rubber gasket - Clear toughened glass - High-efficiency PMMA lens - Integral control gear - Optional surface mounting box for easy wiring or conduit connection when wiring from behind is not possible

Light output 1 (integrated)




Lamp type	LED	CCT	
Nominal lamp power	19 W	CRI	
Total flux	298 lm	LOR	100%
Luminous efficacy	16 lm/W	ULOR	100%
		Total power	19 W

Light output 2 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	19 W	CRI	80
Total flux	611 lm	LOR	100%
Luminous efficacy	32 lm/W	ULOR	100%
		Total power	19 W

Light output 3 (integrated)



Lamp type	LED	CCT	
Nominal lamp power	19 W	CRI	
Total flux	88 lm	LOR	100%
Luminous efficacy	5 lm/W	ULOR	100%
		Total power	19 W

Light output 4 (integrated)



Lamp type	LED	CCT	0 K
Nominal lamp power	19 W	CRI	-18
Total flux	429 lm	LOR	100%
Luminous efficacy	23 lm/W	ULOR	100%
		Total power	19 W

Mounting mode

Wall mounted

Shape and measurements

Length: 5.71 in
Width: 5.71 in
Height: 4.72 in
Weight: 2.8 kg

Adjustability

Fixed

Electric

System power: 76 W
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: III

Protection

IP: 65
IK: 08
Surface temperature: 40°C