

Product data sheet

FLAT BASIC
211401.002
RZB




IP
43

IK
03

Series: FLAT BASIC Decorative round surface-mounted luminaire. Base: plastic. Mouth blown 3-layer opal glass (Triplex glass) with satin finish. Glass fastening: bayonet fixing. Triplex glass produces particularly homogeneous, soft and glare free lighting. Suitable for ceiling mounting, wall (surface). Colour: pure white (RAL#160;9010) Diameter: 500#160;mm Height: 150#160;mm Lamp: LED Socket: without socket Colour temperature: 3000K Colour rendering index (CRI): 80 System power: 19#160;W Rated luminous flux: 2150#160;lm Luminous efficiency: 113#160;lm/W Control gear: AC Strom, dim.Ph.an-/abschnitt Protection class: I Type of protection: IP#160;43

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	19 W	CRI	80
Total flux	2150 lm	LOR	100%
Luminous efficacy	113 lm/W	ULOR	13%
		Total power	19 W

Mounting mode

Ceiling mounted

Shape and measurements

Height: 5.91 in
Diameter: 19.69 in

Adjustability

Fixed

Electric

System power: 19 W

Protection

IP: 43
IK: 03