Product data sheet


EPKL L96 HR
ECOPAK LENS
DEXTRA



IP 20

Ecopak Lens - 1700mm, Surface mounted batten luminaire, White powder painted metal body and steel spine, injection moulded polycarbonate High Rack lens. Options: LE3 - Lithium Emergency LS3 - Lithium Selftest LA3 - Lithium Autotest S - Switch Dimming D - Digital Dimming (DSI) A - Digital Addressable Lighting Interface (DALI) C - Bi-Level Dimming (Corridor Function) H - High Frequency Dimming (Analogue 1-10v) R21E - Reacta 21, On/Off R21C - Reacta 21, Corridor Mode* R44 - Daylight regulating and Occupancy Sensor RCS - Reacta-Control Wireless Sensor RLS - Reacta-Link Wireless Sensor *Bi-Level Dimming. Will only dim the luminaire to 10% during absence and brightout, it will not turn the luminaire off.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	55.3 W	CRI	80
Total flux	9139 lm	LOR	100%
Luminous efficacy	165 lm/W	ULOR	5%
		Total power	55.3 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 68.90 in
Width: 2.76 in
Height: 1.65 in

Adjustability

Fixed

Electric

System power: 55.3 W
Controller: DALI

Integrated sensors

Integrated sensors: Motion sensor, Presence sensor

Protection

IP: 20