



Product data sheet

LD154TG 4.4W 350MA ENB
LD154TG-E3-350-ENB
LIGHTGRAPHIX



LD154TG Ø100mm Trimless Tilted Recessed Uplight. IP67. Constant Current. 4.4W 350mA 10° Extra Narrow beam. The LD154TG is part of our Ultra range, delivering up to 1375lm from a minimal body depth of 85mm including the seamless glass bezel. It features an asymmetric beam with optics set at a 3° tilt, allowing the fitting to be installed further away from the lit surface and focus the light where needed. There are 3 LED engine options available. Our new P1 engine delivers the highest output, whilst the E3 offers an exceptional extra narrow beam of 9°, and the N1, a narrow 13° beam. The lens assembly features large 50mm optics which offer ultra-high efficiency, superior beam quality and low glare. Reaching heights of up to 14 metres and designed with our robust glass bezel, the LD154TG demonstrates an excellent size-to-output ratio, offering a discreet yet powerful exterior solution.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	4.4 W	CRI	85
Total flux	362 lm	LOR	100%
Luminous efficacy	82 lm/W	ULOR	100%
		Total power	4.4 W

Mounting mode

Floor recessed

Shape and measurements

Height: 2.80 in
Diameter: 3.58 in

Adjustability

Fixed

Design

Material impression: Glass

Electric

System power: 4.4 W
Controller: Dimmable 0..10V, Dimmable 1..10V, DMX, DALI
Appliance Class: III

Protection

IP: 67
IK: 09
Designation labels: CE

Other operating numbers

Ambient temperature range: -4...113°F