


Product data sheet

FLAT POLYMERO
672057.002.5
RZB




IP
40

IK
03

Item Number: 672057.002.5 Series: Flat Polymero Type of Protection: IP 40 Protection Class: I Voltage: 220 - 240 V / 0 Hz, 50 - 60 Hz Base: powder coated metal. Cover fastening: push system. Cover: opal plastic (PMMA). Lamps included. Available Colours: white Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 460, , H 120mm Lamp: LED Colour Temperature: 4000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Emergency Lighting System: standard Impact Protection: IK03 (0,35 Joule) Luminaire flux LED: 2100lm System power: 19W Beam Angle: 116° Number of fittings B10A: 31 Number of fittings B16A: 50 Number of fittings C10A: 52 Number of fittings C16A: 85 Inrush current: 5A Unified Glare Ratio: 19,0 EEC: A++

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	19 W	CRI	80
Total flux	2050 lm	LOR	100%
Luminous efficacy	108 lm/W	ULOR	10%
		Total power	19 W

Mounting mode

Wall mounted

Shape and measurements

Height: 4.72 in
Diameter: 18.11 in

Adjustability

Fixed

Electric

System power: 19 W

Protection

IP: 40
IK: 03