

# Product data sheet


URBINO TWILIGHT LED 36W 4250LM 3000K IP66 O6L - FOR PEDESTRIAN CROSSINGS, LEFT SIDE TRAFFIC GRAY II  
130222.5L432.091.986

LUG



Professional streetlight luminaire for LED light sources. Luminaire with twilight sensor. High efficacy to 131 lm/W Mounting: on pillar  $\varnothing 60/76$ mm, on outriggers  $\varnothing 60/76$ mm Body: high pressure die-cast aluminum Lateral Surface Wind Exposed: 0.054 m<sup>2</sup> Power supply efficiency >95% Power: 220-240V 50/60Hz Lifetime (L90B10): 100 000 h Available on request: DALI, DIM 1..10V, LLOC, knife switch, 10kV surge protection, NTC, access to the driver chamber without the use of tools. Additional information: tilt adjustment: -15° to +15° (every 5°). Other remarks: the pole and boom are not part of the luminaire Warranty: 5 years Application: express roads, local roads, town roads, residential area roads, pedestrian crossings, area lighting, avenues, promenade, cycle paths. Type of optics: O6L - for pedestrian crossings, left side traffic

## Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	36 W	CRI	70
Total flux	4250 lm	LOR	100%
Luminous efficacy	118 lm/W	Total power	36 W

## Mounting mode

Pole top mounted

## Shape and measurements

Length: 21.65 in

Width: 9.84 in

Height: 7.68 in

## Adjustability

Tiltable

## Design

Color of housing: Silver gray

## Electric

System power: 36 W

Appliance Class: II

## Integrated sensors

Integrated sensors: Daylight sensor

## Protection

IP: 66

IK: 08