

Product data sheet


LD2B LED 2" ROUND RECESSED DOWNLIGHT
LD2B10D010 EU2B10WFL559024 2LBDSQLC MB
COOPER LIGHTING



IP
47

New construction or retrofit from below; Downlight or lensed wall wash, Excellent light control and low aperture brightness, Installs in shallow or standard plenums; ENERGY STAR® qualified, Round or square die-cast or spun aluminum reflectors, 6 color temperatures: 2400K, 2700K, 3000K, 3500K, 4000K and 5000K CCT, CRI: 80, 90 or 97; D2W™ option from 3000K to 1850K, W2N Tunable White 2700K-6500K or 2000K-5000K, Lumens: 500-2,000; Distributions: 15°, 25°, 40° or 55°, WaveLinx and DLVP connected lighting systems compatibility, Plaster lathing ring accessory offered for flush reflector transition

Light output 1 (integrated)



Lamp type	LED	CCT	2400 K
Nominal lamp power	10.3 W	CRI	90
Total flux	600 lm	LOR	100%
Luminous efficacy	58 lm/W	Total power	10.3 W

Mounting mode

Ceiling recessed

Shape and measurements

Height: 0.39 in
Diameter: 2.00 in

Adjustability

Fixed

Electric

System power: 10.3 W

Protection

IP: 47