Product data sheet


KUBIK POLE 900 1/4/1/0 LED 1,7W E IP65 22 3000K
19.3160.0071.22
LUXIONA



IP 65 IK 09

Outdoor luminaire. Assembly: for the ground. The body material is aluminum. Colour - RAL 9007 (dark grey, metallic, fine structure). Dimensions: 150 x 150 x 900 mm. Diffuser: transparent polycarbonate. The efficiency of the optical system is 81,17%. Beam angle: asymmetric light distribution. Light source type: LED. Colour of the light 3000 K. CRI>80. Lifetime of LED sources: 50000 h L70/B50. Luminaire luminous flux: 604 lm. Power of luminaire: 13 W. Luminaire's light efficiency: 46,5 lm/W. Driver: standard on/off (E). Voltage 220..240 V, 50..60 Hz. Power factor cosφ: >0,5. Circuit load capacity: 37 (B10), 59 (B16), 61 (C10), 89 (C16). Operating temperature range: -25 ÷ 30° C. Protection degree: IP65. Impact resistant: IK09. Protection against electric shock: I.

Light output 1



6 x LED

Nominal lamp power	2.167 W	LOR	52%
Lamp flux	124 lm	Total flux	390 lm
Luminous efficacy	57 lm/W	Total power	13 W
CCT	3000 K		
CRI	80		

Mounting mode

Pole integrated, Standing / Bollard

Shape and measurements

Length: 5.91 in
Width: 5.91 in
Height: 35.43 in

Adjustability

Fixed

Design

Color of housing: Anthracite / graphite, Silver gray

Electric

System power: 13 W
Appliance Class: I

Protection

IP: 65
IK: 09

Other operating numbers

Ambient temperature range: -13...86°F