Product data sheet


LADOR 5 WALL LUMINAIRES
LD-30001-N-8030
LIGMAN



IP 65 IK 08

- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K and 4000 - Die-cast aluminium housing - Pre-treated before powder coating ensuring high corrosion resistance - Thermal heat dissipation body - Single cable entry - Stainless steel fasteners in grade 304 with zinc flake coating (ZFC) - Durable silicone rubber gasket - Clear toughened glass - High-efficiency PMMA lens - Integral control gear - Optional surface mounting box for easy wiring or conduit connection when wiring from behind is not possible

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	3 W	CRI	80
Total flux	243 lm	LOR	100%
Luminous efficacy	81 lm/W	ULOR	100%
		Total power	3 W

Mounting mode

Wall mounted

Shape and measurements

Length: 2.44 in
Width: 2.44 in
Height: 3.62 in
Weight: 0.8 kg

Adjustability

Fixed

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 3 W
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 65
IK: 08
Surface temperature: 40°C