


Product data sheet

LADOR 11 SURFACE EXTERIOR DOWNLIGHTS
LD-80021-N-W40
LIGMAN



- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K and 4000K - Life time L90B10 Ta 25° 135,000, 300,000 - Life time L80B10 Ta 50° 310,000, > 500,000 - Die-cast aluminium housing pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - Stainless steel fasteners in grade 316 - High-efficiency PMMA lens - Durable silicone rubber gasket - Clear toughened glass - Integral control gear

Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	21.7 W	CRI	80
Total flux	1912 lm	LOR	100%
Luminous efficacy	88 lm/W	Total power	21.7 W

Mounting mode

Ceiling mounted, Wall mounted

Shape and measurements

Length: 4.72 in
Width: 4.72 in
Height: 5.04 in
Weight: 2.1 kg

Adjustability

Fixed

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 21.7 W
Voltage: 230 V AC
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 65
IK: 07
Surface temperature: 40°C