

Product data sheet

STREET LIGHTING
V1-S1-90648-40U24-6602530 LEVANTE PARKING 25W 3000K NEMA
VARTON




IP
66

IK
03

LED street light luminaire with a concise design. Adjustable spigot. Cast aluminum housing. Application: parking, squares, parks. Installation: pole mounted and side-entry mounted (Ø40mm-48mm/Ø48mm-60mm) Power factor: 0,95 Ingress protection (IP): IP66 Impact resistance: IK03 Protection class: I AC frequency, Hz: 50 Flicker, %: 3 Climatic modification and category of placement: УХЛ1 Color rendering index: 70-79 Nominal voltage, V: 220...230 <https://www.varton.ru/products/ulichnoe-osveshchenie/levante/levante-parking-dlya-parkovki/svetodiodnyy-svetilnik-varton-ulichnyy-levante-parking-25-vt-kronshteyn-48-mm-3000-k-1-10v-nema-ra19/>

Light output 1



1 x LED			
Nominal lamp power	25 W	LOR	100%
Lamp flux	3400 lm	Total flux	3400 lm
Luminous efficacy	136 lm/W	Total power	25 W
CCT	3000 K		
CRI	70		

Mounting mode

Pole integrated

Electric

System power: 25 W

Shape and measurements

Length: 23.46 in

Width: 5.35 in

Height: 3.98 in

Protection

IP: 66

IK: 03

Adjustability

Fixed