
Product data sheet

BARIS 40 LED UGR PLUS N 4350LM I KL. IP20 1421MM 840 35W ANODA CO 60D
769269
LENA LIGHTING



769269 BARIS 40 LED UGR PLUS N 4350lm I kl. IP20 1421mm 840 35W Anoda CO 60D The BARIS 40 LED UGR PLUS luminaire was created to provide maximum comfort and work efficiency. With a UGR (Unified Glare Rating) value below 19, it minimizes the glare effect, affecting well-being, reducing fatigue and reducing the number of errors made. Suspended or surface-mounted lighting lamp with a very narrow cross-section. Its body is made of anodized aluminum profile in gray or aluminum profile painted white or black (other colors available on request). The optical system is in the form of a lens with a parabolic louver.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	35 W	CRI	80
Total flux	4350 lm	LOR	100%
Luminous efficacy	124 lm/W	Total power	35 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 55.94 in
Width: 1.57 in
Height: 2.09 in

Adjustability

Fixed

Design

Material impression: Aluminum
Color of housing: Silver gray

Electric

System power: 35 W
Appliance Class: I

Protection

IP: 20
IK: 03
Designation labels: CE