


Product data sheet

VIVO M LED2800-840 3CV FL-S WHM
60714753
ZUMTOBEL



LED spotlight with stabilised colour temperature "Essential stableWhite"; optimised for efficient and high-output accent lighting for shops and showrooms; compact, timeless spotlight design; innovative thermal design achieves passive cooling; Luminaire with 3-phase universal adapter with control gear unit in trackbox adapter (only for Zumtobel 3-phase/L3+DALI track), ; lamp(s): 1/24W LED2800-840; Colour rendering Ra > 80, colour temperature 4000 K (neutral white); Luminaire or spotlight with FLOOD light distribution, with rotationally symmetrical reflector in silver colour; Chromaticity tolerance (initial MacAdam): 3; Luminaire luminous flux: 2800 lm, Luminaire efficacy: 117 lm/W; service life: 50000 h for luminous flux at 80% of initial value; UVA-free and IR-free light; total power: 24 W; mains voltage: 220-240V/ 50/60Hz; spotlight can rotate through 360° and tilt through 90°; spotlight housing made of die-cast aluminium, surface finish: microtextured paint in white; control box of polycarbonate; excellent glare reduction via front ring of polycarbonate, black; front ring used for attaching accessories; specular reflector made of polycarbonate aluminium-sputtered, mirrorbrite, iridescent-free; specular reflector designed to be interchangeable and retrofitted; dimensions: 99x150x222 mm; weight: 1.3 kg; Note: not suitable for point outlets.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	24 W	CRI	80
Total flux	2800 lm	LOR	100%
Luminous efficacy	117 lm/W	Total power	24 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 3.90 in
Width: 5.91 in
Height: 8.74 in
Weight: 1.3 kg

Design

Material impression: Aluminum
Color of housing: White

Electric

System power: 24 W
Voltage: 220-240 V AC
Appliance Class: I

Protection

IP: 20
Designation labels: CE