

# Product data sheet

FLAT POLYMERO KREIS  
311951.002.4.191  
RZB




IP  
40

IK  
10

Series: FLAT POLYMERO KREIS Decorative round surface-mounted luminaire. Base: metal, powder-coated. Diffuser made of plastic (polycarbonate), opal, shockproof. Diffuser fastening: patented push system. Suitable for ceiling mounting, wall (surface). Slave luminaire. Can only be operated in combination with corresponding master luminaire. Colour: white Diameter: 360&#160;mm Height: 87&#160;mm Lamp: LED Socket: without socket Colour temperature: 4000K Colour rendering index (CRI): 83 System power: 21&#160;W Rated luminous flux: 2150&#160;lm Luminous efficiency: 102&#160;lm/W Control gear: Converter not necessary Protection class: I Type of protection: IP&#160;40

## Light output 1 (integrated)



|                    |          |             |        |
|--------------------|----------|-------------|--------|
| Lamp type          | LED      | CCT         | 4000 K |
| Nominal lamp power | 21 W     | CRI         | 80     |
| Total flux         | 2150 lm  | LOR         | 100%   |
| Luminous efficacy  | 102 lm/W | ULOR        | 13%    |
|                    |          | Total power | 21 W   |

## Mounting mode

Ceiling mounted

## Shape and measurements

Height: 3.43 in  
Diameter: 14.17 in

## Adjustability

Fixed

## Electric

System power: 21 W

## Protection

IP: 40  
IK: 10