


# Product data sheet

KTY234 [R65] IP66:LED-3/9W/3K  
114-9085  
WE-EF



IP66, Class I. IK10. Marine-grade, all-aluminium construction. 5CE superior corrosion protection including PCS hardware. Polycarbonate lens. Silicone CCG® Controlled Compression Gasket. Luminaire is factory-sealed and does not need to be opened during installation. Integral EC electronic converter in thermally-separated compartment. Advanced thermal management protects LEDs while optimising lumens output. CAD-optimised optics for superior illumination and glare control. Two-sided light output versions for 360° symmetric distribution. One-sided light output versions with 'rearward glow' feature. Ideal for pathway lighting applications. Luminaire spacing up to 5-8 m.

## Light output 1



|                    |         |             |        |
|--------------------|---------|-------------|--------|
| 3 x LED            |         |             |        |
| Nominal lamp power | 3 W     | LOR         | 69%    |
| Lamp flux          | 430 lm  | Total flux  | 892 lm |
| Luminous efficacy  | 81 lm/W | Total power | 11 W   |
| CCT                | 3000 K  |             |        |
| CRI                | 80      |             |        |

## Mounting mode

Standing / Bollard

## Shape and measurements

Height: 39.92 in  
Diameter: 7.09 in  
Weight: 9 kg

## Electric

System power: 11 W  
Appliance Class: I

## Protection

IP: 66