

Product data sheet

NUMINOS DL M
1003889
SLV




IP
44


IK
02

NUMINOS is the best possible coordinated light system from SLV that combines function, design and technology. With different downlights and spotlights, you can experience a thousand lighting design possibilities. This also includes NUMINOS® DL M, which impresses as a recessed ceiling light with the best workmanship and lighting quality. Ideal for discreet, modern and space-saving lighting that draws the focus to objects or the room. The recessed ceiling light convinces with a power consumption of 17.55 watts, luminous flux of 1660 lumens, colour temperature of 4000 Kelvin and a colour reproduction index of 90. This means that easy installation is a mere formality. When to choose NUMINOS from SLV – modular diversity awaits you.


Light output 1



1 x LED			
Nominal lamp power	20 W	LOR	100%
Lamp flux	1119 lm	Total flux	1119 lm
Luminous efficacy	54 lm/W	Total power	20.89 W
CCT	3966 K		
CRI	91		



1 x LED			
Nominal lamp power	20 W	LOR	100%
Lamp flux	1418 lm	Total flux	1418 lm
Luminous efficacy	68 lm/W	Total power	20.99 W
CCT	3966 K		
CRI	91		



1 x LED			
Nominal lamp power	21 W	LOR	100%
Lamp flux	1617 lm	Total flux	1617 lm
Luminous efficacy	76 lm/W	Total power	21.2 W
CCT	3966 K		
CRI	91		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 4.13 in

Width: 4.13 in

Height: 2.68 in

Weight: 0.205 kg

Adjustability

Fixed

Electric

System power: 20.89-21.2 W

Protection

IP: 44

IK: 02