



# Product data sheet

MINGATA MINI  
612283.004.76.N  
RZB



Series: MINGATA INTERNATIONAL mini Functional pole-side and pole-top luminaire in a modern design. Housing made of corrosion-resistant die-cast aluminium, seawater resistant powder-coated. Pole-top fixing with integrated cable routing and stainless steel screws. With membrane valve as a standard to avoid condensed water. Tilt angle can be adjusted and locked in 5 degree steps featuring angular scale. Cover clear single-pane toughened glass. 1 x LED module with 96 LEDs. One piece multi-layer lens cover. Asymmetrical light distribution (Side Throw). Luminaires for spigot Ø 42 mm. Tool-free maintenance / replacement by Eccentric-Lock system with disconnect plug and Hybrid-Lock-System. DALI control gear with integrated surge protection up to 10 kV. With NFC programming interface. Constant light output (CLO). Luminaire built-in 10kV surge protector (L,N,Earth). Pre-assembled connection cable 3 x 1.5 mm<sup>2</sup> (H07RN-F), length 12.5 m. 7-Pin NEMA-socket with shorting cap. Colour: silver, matt (approx. RAL 9006) Length: 530 mm Width: 270 mm Height: 100 mm Lamp: LED System power: 15 W Rated luminous flux: 1950 lm Luminous efficacy: 130 lm/W Control gear: Converter, dimmable, DALI Protection class: I Type of protection: IP 66

## Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	15 W	CRI	70
Total flux	1950 lm	LOR	100%
Luminous efficacy	130 lm/W	ULOR	13%
		Total power	15 W

## Mounting mode

Pole top mounted

## Shape and measurements

Length: 10.63 in  
Width: 20.87 in  
Height: 3.94 in

## Adjustability

Fixed

## Design

Color of housing: Silver gray

## Electric

System power: 15 W

## Protection

IP: 66  
IK: 08