## Product data sheet

LUCAS IV (WALL FITTING BEADED) 9.834.2056.16

LEIPZIGER LEUCHTEN









Mounting heights between 4.00 - 6.00 m. - High-quality mirror optics to suit non-glare class KB1 - Aluminium cast luminaire body, inside white, outside painted in colour - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Luminaires with wiring ready for connection - Easy installation with adapter jack - Scope of supply includes complete unit with one/two painted special steel brackets -Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

## Light output 1



| 1 x High pressure sodium vapour lamp |          |  |
|--------------------------------------|----------|--|
| Nominal lamp power                   | 100 W    |  |
| Lamp flux                            | 10400 lm |  |
| Luminous efficacy                    | 75 lm/W  |  |
| CCT                                  | 2000 k   |  |
| CRI                                  | 25       |  |

| LOR         | 83%     |
|-------------|---------|
| ULOR        | 2%      |
| Total flux  | 8621 lm |
| Total power | 115 W   |
|             |         |



| 1 x High pressure sodium vapour lamp |         |             |         |  |  |
|--------------------------------------|---------|-------------|---------|--|--|
| Nominal lamp power                   | 70 W    | LOR         | 83%     |  |  |
| Lamp flux                            | 5600 lm | ULOR        | 2%      |  |  |
| Luminous efficacy                    | 56 lm/W | Total flux  | 4642 lm |  |  |
| CCT                                  | 2000 K  | Total power | 83 W    |  |  |
| CRI                                  | 25      |             |         |  |  |

Mounting mode

Wall mounted

Shape and measurements

Height: 22.44 in Diameter: 22.44 in Electric

System power: 83-115 W

Protection

IP: 55