# Product data sheet

23011 LED CG-S MIT KLARER SCHEIBE 40071350165 + 40071345985

EATON EMERGENCY LIGHTING








• Safety luminaire for recessed ceiling mounting • Special LED optical arrangement for efficient illumination of escape routes, suitable for mounting heights up to 7 m, maximum distance from luminaire to luminaire: > 16 m from 3 m mounting height and > 20 m from 4.5 m mounting height • Minimum maintenance required due to high service life of the LEDs (over 50,000 hours) • Shortened inspection effort due to CEWA GUARD technology • Automatic function monitoring of up to 20 luminaires per circuit • Reduced installation costs with STAR technology

• Freely programmable mixed operation of the switching modes per luminaire in one circuit

## Light output 1 (integrated, emergency)



Lamp type	LED	CCT	6500 K
Nominal lamp power	4.4 W	CRI	70
Total flux	107 lm	LOR	100%
Luminous efficacy	24 lm/W	Total power	4.4 W

#### Mounting mode

Ceiling recessed

### Shape and measurements

Length: 14.92 in Width: 9.29 in Height: 2.56 in

## Adjustability

Fixed

### Design

Color of housing: Silver gray

#### Electric

System power: 4.4 W

Suitable for feed-through wiring

Appliance Class: I

## Information regarding emergency functions

Emergency lighting only

Emergency power supply: Central battery feed-in

Emergency sign: N/A

# Protection

IP: 41 IK: 03