

Product data sheet

LOUIS I (1-ARMED)
9.615.2056.07
LEIPZIGER LEUCHTEN




Mounting height of 3.00 to 4.50 m for medium light requirements - Impact-resistant clear polycarbonate cylinder, UV-stabilized - Mirror lamellae for light guidance and glare limitation made of premium highest-grade aluminium, burnished and anodized - Aluminium reflector finished in special white paint for max. light reflection - Aluminium cover painted - Unit carrier made of corrosion-resistant cast aluminium, painted - All electrical components arranged on a block - Connection with adapter jack - Available in any RAL or DB colour without surcharge - Order pole, dia. 76 mm, separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

Light output 1



1 x High pressure sodium vapour lamp

Nominal lamp power	100 W	LOR	56%
Lamp flux	10400 lm	ULOR	14%
Luminous efficacy	51 lm/W	Total flux	5815 lm
CCT	2000 K	Total power	115 W
CRI	25		



1 x High pressure sodium vapour lamp

Nominal lamp power	70 W	LOR	56%
Lamp flux	5600 lm	ULOR	14%
Luminous efficacy	38 lm/W	Total flux	3131 lm
CCT	2000 K	Total power	83 W
CRI	25		

Mounting mode

Pole top mounted

Shape and measurements

Height: 23.23 in

Diameter: 7.87 in

Design

Material impression: Matt

Color of housing: White

Electric

System power: 83-115 W

Ballast: ECG

Suitable for feed-through wiring

Protection

IP: 55

Designation labels: CE

Other operating numbers

Ambient temperature range: -4...95°F