


Product data sheet


LED ECO PANEL 0312B 36W 865 H
4058075753235
LEDVANCE



IP
20

Latest backlit LED technology platform. Available in 3 metric sizes: 600x600, 300x1200, 600x1200mm. Standard CCT: 4000K, 6500K & 3000K. High color rendering: CRI > 80. High power factor: PF>0.90. Recess mount with optional plaster ceiling mounting clips and suspension kit. Flicker free driver. EMC suppression circuit in driver. Sturdy SPCC housing. Safety compliance certificates: CB, EU RoHS 2.0. Integrated heat resistance lens for uniform light distribution, reduce product height to only 34mm. Long 50,000hr lifetime reduces maintenance costs. Fast connector between panel and driver for easy installation and maintenance. Seamless aluminum frame elegant design. IP40 protection from diffuser side suitable for different installations.

Light output 1 (integrated)



Lamp type	LED	CCT	6800 K
Nominal lamp power	36 W	CRI	80
Total flux	3240 lm	LOR	100%
Luminous efficacy	90 lm/W	Total power	36 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 45.39 in

Width: 9.96 in

Height: 0.39 in

Adjustability

Fixed

Electric

System power: 36 W

Protection

IP: 20