



Product data sheet

P.THIRTY SUSP. X-SEG.HOR. SILVER DI/ID OBD
P30-HXFH9006C2927H3G
PLANLICHT




LED HO 2700K 26,2W 3120lm DALI CRI90 <https://katalog.planlicht.com/en-gb/search?q=p.thirty&type=1-profile-segment>

Light output 1 (integrated)




Lamp type	LED	CCT	2700 K
Nominal lamp power	3.28 W	CRI	90
Total flux	390 lm	LOR	100%
Luminous efficacy	119 lm/W	Total power	3.28 W

Light output 2 (integrated)




Lamp type	LED	CCT	2700 K
Nominal lamp power	3.28 W	CRI	90
Total flux	390 lm	LOR	100%
Luminous efficacy	119 lm/W	Total power	3.28 W

Light output 3 (integrated)




Lamp type	LED	CCT	2700 K
Nominal lamp power	3.28 W	CRI	90
Total flux	390 lm	LOR	100%
Luminous efficacy	119 lm/W	Total power	3.28 W

Light output 4 (integrated)




Lamp type	LED	CCT	2700 K
Nominal lamp power	3.28 W	CRI	90
Total flux	390 lm	LOR	100%
Luminous efficacy	119 lm/W	Total power	3.28 W

Light output 5 (integrated)




Lamp type	LED	CCT	2700 K
Nominal lamp power	3.28 W	CRI	90
Total flux	390 lm	LOR	100%
Luminous efficacy	119 lm/W	Total power	3.28 W

Light output 6 (integrated)




Lamp type	LED	CCT	2700 K
Nominal lamp power	3.28 W	CRI	90
Total flux	390 lm	LOR	100%
Luminous efficacy	119 lm/W	Total power	3.28 W

Light output 7 (integrated)



Lamp type	LED	CCT	2700 K
Nominal lamp power	3.28 W	CRI	90
Total flux	390 lm	LOR	100%
Luminous efficacy	119 lm/W	Total power	3.28 W

Light output 8 (integrated)



Lamp type	LED	CCT	2700 K
Nominal lamp power	3.28 W	CRI	90
Total flux	390 lm	LOR	100%
Luminous efficacy	119 lm/W	Total power	3.28 W

Mounting mode

Pendant

Shape and measurements

Length: 8.46 in

Width: 28.43 in

Height: 1.38 in

Adjustability

Fixed

Electric

System power: 26.2 W

Protection

IP: 20

Designation labels: CE