Product data sheet

BENTO XS
BENTO-XS-ASY13-16LED-2200K-016-350 MA
RAGNI



IP 66

Made of aluminium and featuring symmetrical lines, Bento is a functional luminaire with a minimalist design available in 3 sizes. Rectangular in shape, it has a compartment at the back that houses the control gear, harmoniously joining the lighting part. The fins on the top of the luminaire promote heat dissipation. It has a double compartmentalisation and is fully IP66. Its sleeve is adaptable for side or top mounting (with inclination from -15° to 15°). Bento receives from 12 to 24 LEDs in the S version, 24 to 48 LEDs in the M version and 72 LEDs in the L version, with a colour temperature of 3000 K or 4000 K and offers 3 asymmetric light distributions. The Bento luminaire incorporates the Zhaga standard in its design.

Light output 1



1 x LED

Nominal lamp power	18.2 W	LOR	100%
Lamp flux	2369 lm	Total flux	2369 lm
Luminous efficacy	130 lm/W	Total power	18.2 W
CCT	2200 K		
CRI	70		

Mounting mode

Pole top mounted

Shape and measurements

Length: 19.69 in
Width: 7.87 in
Height: 3.94 in

Adjustability

Fixed

Electric

System power: 18.2 W

Protection

IP: 66