

# Product data sheet

GUIDELED SL 13042 CG-S


40071353482

EATON EMERGENCY LIGHTING



• Safety luminaire in LED technology for surface mounting • Low profile of only 30 mm • Unobtrusive appearance ensured by optics integrated in the luminaire • Suitable for mounting heights up to 28 m by narrow beam optics and exceptionally efficient HighPower LEDs • Spacing up to 24 m from luminaire to luminaire with optics for escape route illumination • Up to 15 m from luminaire to luminaire with optics for open area illumination • Minimum service requirement due to high service life of the LEDs (50 000 hours)

## Light output 1 (integrated, emergency)



Lamp type	LED	CCT	6500 K
Nominal lamp power	5 W	CRI	70
Total flux	168 lm	LOR	100%
Luminous efficacy	34 lm/W	Total power	5 W

## Mounting mode

Ceiling mounted

## Shape and measurements

Length: 5.51 in

Width: 5.51 in

Height: 1.18 in

## Adjustability

Fixed

## Design

Color of housing: White

## Electric

System power: 5 W

Suitable for feed-through wiring

Appliance Class: I

## Information regarding emergency functions

Emergency lighting only

Emergency power supply: Central battery feed-in

Emergency sign: N/A

## Protection

IP: 41

IK: 03