


# Product data sheet

HALOSCAN CLIP HP 92735  
23120 9230  
DELTA LIGHT




Luminaire, ceiling recessed or ceiling surface mounted (indoor use) from Deltalight, named HALOSCAN CLIP HP 92735, available in the colour(s): black, white. For recessed mounting, a round opening with a diameter of 51 mm is needed and a min. depth for recessing of 40 mm. This luminaire is equipped with LED array 11,6W / CRI>90 (R9: 60) / 2700K / 1458lm with an optional driver, suitable for currents of 350mA. Light distributor: lens 35°.


## Light output 1




1 x LED			
Nominal lamp power	12 W	LOR	73%
Lamp flux	1458 lm	Total flux	1061 lm
Luminous efficacy	122 lm/W	Total power	12 W
CCT	2700 K		
CRI	90		




1 x LED			
Nominal lamp power	12 W	LOR	73%
Lamp flux	1458 lm	Total flux	1061 lm
Luminous efficacy	122 lm/W	Total power	12 W
CCT	2700 K		
CRI	90		




1 x LED			
Nominal lamp power	12 W	LOR	73%
Lamp flux	1458 lm	Total flux	1061 lm
Luminous efficacy	122 lm/W	Total power	12 W
CCT	2700 K		
CRI	90		



1 x LED			
Nominal lamp power	12 W	LOR	73%
Lamp flux	1458 lm	Total flux	1061 lm
Luminous efficacy	122 lm/W	Total power	12 W
CCT	2700 K		
CRI	90		



1 x LED			
Nominal lamp power	12 W	LOR	73%
Lamp flux	1458 lm	Total flux	1061 lm
Luminous efficacy	122 lm/W	Total power	12 W
CCT	2700 K		
CRI	90		



1 x LED			
Nominal lamp power	12 W	LOR	73%
Lamp flux	1458 lm	Total flux	1061 lm
Luminous efficacy	122 lm/W	Total power	12 W
CCT	2700 K		
CRI	90		

**Mounting mode**

Ceiling mounted

**Shape and measurements**

Height: 0.04 in

Diameter: 2.28 in

**Electric**

System power: 12 W

Appliance Class: II

**Protection**

IP: 20

Designation labels: CE