


Product data sheet

PRO-AQUA III, 60CM
40281600
PROLUMIA




Light source: LED SMD2835 Beam angle: 120° Color temperature: 4000K Light output: Switchable (4 positions) Color rendering index: Ra >80
Operating temperature: -25°C – +40°C Rated life hours: L70 > 50.000 (L70 > 50,000) LED driver (included): CE (Osram) Input: 220 - 240V AC
50-60Hz Power factor: >0,90 (>0.90) Safety class: Class II

Light output 1




1 x LED

Nominal lamp power	18 W	LOR	100%
Lamp flux	2700 lm	Total flux	2700 lm
Luminous efficacy	150 lm/W	Total power	18 W
CCT	4500 K		
CRI	80		




1 x LED

Nominal lamp power	15 W	LOR	100%
Lamp flux	2250 lm	Total flux	2250 lm
Luminous efficacy	150 lm/W	Total power	15 W
CCT	4500 K		
CRI	80		



1 x LED

Nominal lamp power	12 W	LOR	100%
Lamp flux	1800 lm	Total flux	1800 lm
Luminous efficacy	150 lm/W	Total power	12 W
CCT	4500 K		
CRI	80		



1 x LED

Nominal lamp power
 Lamp flux
 Luminous efficacy
 CCT
 CRI

10 W
 1500 lm
 150 lm/W
 4500 K
 80

LOR
 Total flux
 Total power

100%
 1500 lm
 10 W

Mounting mode

Ceiling recessed, Wall mounted

Shape and measurements

Length: 2.95 in
 Width: 23.90 in
 Height: 2.76 in

Electric

System power: 10-18 W
 Appliance Class: 0

Integrated sensors

Integrated sensors: Motion sensor

Protection

IP: 66
 IK: 08
 Designation labels: CE