


# Product data sheet

GUSTAV I (WALL FITTING)  
9.744.2036.07  
LEIPZIGER LEUCHTEN




Mounting height of 3.00 to 4.50 m for medium light requirements - Impact-resistant clear polycarbonate cylinder, UV-stabilized - Mirror lamellae for light guidance and glare limitation made of premium highest-grade aluminium, burnished and anodized - Aluminium reflector finished in special white paint for max. light reflection - Aluminium cover painted - Unit carrier made of corrosion-resistant cast aluminium, painted - All electrical components arranged on a block - Connection with adapter jack - Available in any RAL or DB colour without surcharge  
Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

## Light output 1



### 1 x High pressure sodium vapour lamp

Nominal lamp power	50 W	LOR	54%
Lamp flux	3500 lm	ULOR	11%
Luminous efficacy	30 lm/W	Total flux	1878 lm
CCT	2000 K	Total power	62 W
CRI	25		



### 1 x High pressure sodium vapour lamp

Nominal lamp power	70 W	LOR	54%
Lamp flux	5600 lm	ULOR	11%
Luminous efficacy	36 lm/W	Total flux	3004 lm
CCT	2000 K	Total power	83 W
CRI	25		

## Mounting mode

Wall mounted

## Shape and measurements

Height: 9.84 in  
Diameter: 9.84 in

## Design

Material impression: Matt  
Color of housing: White

## Electric

System power: 62-83 W  
Ballast: ECG  
Controller: DALI

## Protection

IP: 55  
Designation labels: CE

## Other operating numbers

Ambient temperature range: -13...95°F