


Product data sheet

CADERO QUADRA
672295.004.1
RZB




IP
65

IK
05

Item Number: 672295.004.1 Series: Cadero Type of Protection: IP 65 Protection Class: I Voltage: 220 - 240 V / 0 Hz, 50 Hz, 60 Hz Housing made of corrosion-resistant die-cast aluminium for outdoor use, powder-coated. Cover with crystal glass frosted inside. Screwless installation of the cover with latch. Installation outside the sealed area with compensation for drill hole tolerance. Lamp (mains voltage LED module)included. Fitted as standard with diaphragm valve to prevent condensation. With second cable entry for loop-through. Operating in DC mode with reduced luminous flux! Available Colours: silver, metallic Type of Installation: Ceiling mounting, Wall (surface) Dimensions: L 257, B 257, H 81mm Lamp: LED Colour Temperature: 4000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Emergency Lighting System: standard Safety Marks: F-mark Impact Protection: IK05 (0,70 Joule) Luminaire flux LED: 660lm System power: 13W Beam Angle: 128° Unified Glare Ratio: 22,4 EEC: A+

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	13 W	CRI	80
Total flux	660 lm	LOR	100%
Luminous efficacy	51 lm/W	ULOR	5%
		Total power	13 W

Mounting mode

Wall mounted

Shape and measurements

Length: 10.12 in
Width: 10.12 in
Height: 3.19 in

Adjustability

Fixed

Electric

System power: 13 W

Protection

IP: 65
IK: 05