Product data sheet


MORFI_PETAL_54W_24V_DC_WARM_D800MM
82000412_
PETRIDIS



IP 20

Morfi is not just a customised product with an innovative design, but also a working tool for the lighting designers and engineers. It combines the aesthetic with the latest LED technological standards and meets the various needs of the customers in a bespoke way: it allows them to “think big” offering totally unexpected results even to large scale projects. Technical Features - Aluminium body, painted electrostatically in selected colour. - High efficient polycarbonate satin cover. - Direct / Indirect illumination. - Pure light without IR/UV radiation. - Operation life: 50,000 hours with efficiency > 80% of the initial luminous flux (L80B10). - Connection for operation on 230V/50Hz. Upon Request - At special shapes and dimensions. - Connection for operation on 230V-50/60Hz with dimmer dali or 1-10VDC ballast. ----------Details for Dialux: Morfi Petal - 18pcs R 0.400m End Angle 260

Light output 1



1 x LED

Nominal lamp power	3 W	LOR	57%
Lamp flux	400 lm	Total flux	229 lm
Luminous efficacy	133 lm/W	Total power	3 W
CCT	3000 K		
CRI	80		

Mounting mode

Pendant, Ceiling mounted

Shape and measurements

Length: 3.94 in
Width: 1.89 in
Height: 0.98 in

Adjustability

Fixed

Design

Material impression: Aluminum, Plastic

Electric

System power: 3 W
Controller: Dimmable 1..10V, DALI
Appliance Class: III

Protection

IP: 20
Designation labels: CE