Product data sheet

BEAMLINE SLIM
742167.0025.1.76
RZB



IP 20 IK 06

Series: BEAMLINE SLIM Linear surface mounted projector for aesthetically sophisticated lighting. Housing: metal, powder-coated. Perfect heat management with an aluminium heat sink. Rotation range: 356°. Swivel range: 90°. LED light unit with MRS technology: Mini-Reflector-System made of metallised thermoplastic with prismatic white glare-suppressing frame for pleasant glare-free light (RUG < 10). Narrow beam light distribution. With adapter for RZB 3-circuit DALI tracks. Suitable for Track on ceiling, Wall track. Converter integrated in the adapter. Colour: traffic white, matt (RAL 9016) Length: 145 mm Width: 35 mm Height: 80 mm Lamp: LED Socket: without socket Colour temperature: 3000K Colour rendering index (CRI): 90 System power: 14 W Rated luminous flux: 980 lm Beam angle Down: 12° Luminous efficiency: 70 lm/W Control gear: Converter, dimmable, DALI Protection class: II Type of protection: IP 20

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	14 W	CRI	90
Total flux	980 lm	LOR	67%
Luminous efficacy	70 lm/W	ULOR	14%
		Total power	14 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 1.38 in
Width: 5.71 in
Height: 3.15 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 14 W

Protection

IP: 20
IK: 06