


Product data sheet

TX-MOVE
901854.002.76
RZB




Series: TX-MOVE Einlege/Einbau-Flächenstrahler. Housing: aluminium, powder-coated. 2xSwivel range: 90°. High-efficiency LED units with optimum light control thanks to clear plastic (PC) lens optics. Special microstructures reduce the yellow corona (caused by chromatic aberration). Symmetrical light distribution. Suitable for laying in grid ceiling module 625. Connected converter included in separate gearbox. Suitable for through-wiring. MultiLumen: Luminous flux variable in 3 steps. Accessories: Mounting frame for installation in suspended ceilings. Replaceable components make repairs possible and extend the service life. Zwei DALI-Betriebsgeräte für zwei separate DALI-Adressierungen. Colour: traffic white, matt (RAL 9016) Length: 622 mm Width: 190 mm Height: 39 mm Cut-out length: 602 mm Cut-out width: 174 mm Recess height: 100 mm Lamp: LED Socket: without socket Colour temperature: 3000K Colour rendering index (CRI): 80 System power: 35 W Rated luminous flux: 5600 lm Beam angle Down: 62° Luminous efficiency: 160 lm/W System power 2: 47 W Rated luminous flux 2: 7250 lm Luminous efficiency 2: 154 lm/W System power 3: 68 W Rated luminous flux 3: 9850 lm Luminous efficiency 3: 145 lm/W Control gear: Converter, dimmable, DALI Protection class: I Type of protection: IP 20


Light output 1



1 x LED			
Nominal lamp power	34 W	LOR	100%
Lamp flux	4925 lm	ULOR	13%
Luminous efficacy	145 lm/W	Total flux	4925 lm
CCT	3000 K	Total power	34 W
CRI	80		



1 x LED			
Nominal lamp power	23.5 W	LOR	100%
Lamp flux	3625 lm	ULOR	13%
Luminous efficacy	154 lm/W	Total flux	3625 lm
CCT	3000 K	Total power	23.5 W
CRI	80		


**1 x LED**

Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

17.5 W
2800 lm
160 lm/W
3000 K
80

LOR
ULOR
Total flux
Total power

100%
13%
2800 lm
17.5 W


Light output 2**1 x LED**

Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

34 W
4925 lm
145 lm/W
3000 K
80

LOR
ULOR
Total flux
Total power

100%
13%
4925 lm
34 W


**1 x LED**

Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

23.5 W
3625 lm
154 lm/W
3000 K
80

LOR
ULOR
Total flux
Total power

100%
13%
3625 lm
23.5 W

**1 x LED**

Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

17.5 W
2800 lm
160 lm/W
3000 K
80

LOR
ULOR
Total flux
Total power

100%
13%
2800 lm
17.5 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 7.48 in
Width: 24.49 in
Height: 1.54 in

Adjustability

Rotatable, Tilttable

Design

Color of housing: White

Electric

System power: 35-68 W

Protection

IP: 20
IK: 04