

Product data sheet


ALFONS II FF LED (ASYMMETRICAL)
9.140.8418.04-3
LEIPZIGER LEUCHTEN



IP
66

recom. pole height: 6.00m – 12.00m light standards: low, medium and high lighting requirements lamp: incl. 1, 2, 3 or 4 FF IV-X LED module(s), easy to replace colour temperature: 3.000K warm white or 4.000K neutral white LED gear: electronic driver, up to 100.000 hours; driver with integrated Constant Light Output (CLO) in order to keep the luminous flux at the same level over the entire lifetime LED life expectancy: up to 100.000 hours, 50.000 hours/ L100 for minimum maintenance costs due to an excellent thermal management light control: at extra cost: power reduction, dimming or CLEVER LIGHT optical system: directed light (multi layer) provided by an exchangeable, anti-aging lens technology light distribution: asymmetrical luminaire head: die cast aluminium, powder coated colour: DB 703; other colours on request glazing: flat, clear toughened glass glazing wiring: completely wired; via a plug and socket connector within the luminaire head; luminaire head to be hinged upward installation: for top or side entry; ASA 60 or ASA 76 to be ordered separately: • ASA 60 for side entry \varnothing 48mm up to 60mm (0°, -5°, -10°, -15°) or for top entry \varnothing 60mm (0°, 5°, 10°, 15°) • ASA 76 for top entry \varnothing 76mm (0°, 5°, 10°) accessory: adapter ASA, column, pole accessories, wall bracket, cable – to be ordered separately application areas: parks, boulevards, schools, home for elderly people, hotels, factory premises, residential and local distribution roads, main streets, car parks, pedestrian and cycle lanes, holiday parks

Light output 1 (integrated)



| | | | |
|--------------------|----------|-------------|--------|
| Lamp type | LED | CCT | 3000 K |
| Nominal lamp power | 68 W | CRI | 70 |
| Total flux | 8430 lm | LOR | 100% |
| Luminous efficacy | 124 lm/W | Total power | 68 W |

Mounting mode

Pole integrated, Pole top mounted

Shape and measurements

Length: 29.13 in
Width: 13.98 in
Height: 7.68 in
Weight: 12.5 kg

Adjustability

Height adjustable

Electric

System power: 68 W

Protection

IP: 66