


# Product data sheet

FREESTANDING LUMINAIRE LIGHTPAD OFFICE FOR TWO PERSON WORKS  
2007.8097 - LGTPD4 CCMH LED13600-940 WH 0IF SEDI CH  
REGENT




Freestanding luminaire Lightpad Office for two person workstation, central, well-spaced, with LED, system power: 102 W, standby power 2 x 0.5 W, luminous flux of luminaire 13600 lm, colour rendering index CRI > 90, colour temperature 4000 K, neutral white, colour tolerances SDCM 3, lifetime LED L90 50'000 h, office-compatible and glare-free according to EN 12464-1 ( $UGR < 19$ ;  $L_{max} \geq 65^\circ \leq 3000 \text{ cd/m}^2$ ), photobiological safety: the luminaire poses no danger (RG0), 230 V, direct-indirect light emission, without control element, in aluminium, white, RAL 9016, 2 integral control gears, SensoDim®, with 2 light/movement sensors, 3m power supply cable with plug, base plate, H-shaped, ENEC certified, protection class I, ingress protection IP20, glow wire test 650 °C, this product contains a light source of energy efficiency class A and EPREL registration number: 1258594 L = 718 mm, B = 906 mm, H = 19 mm, total height = 2000 mm

## Light output 1



1 x LED			
Nominal lamp power	51 W	LOR	100%
Lamp flux	6800 lm	ULOR	64%
Luminous efficacy	133 lm/W	Total flux	6789 lm
CCT	4000 K	Total power	51 W
CRI	90		

## Light output 2



1 x LED			
Nominal lamp power	51 W	LOR	100%
Lamp flux	6800 lm	ULOR	64%
Luminous efficacy	133 lm/W	Total flux	6789 lm
CCT	4000 K	Total power	51 W
CRI	90		

## Mounting mode

Standing / Bollard

## Shape and measurements

Length: 28.27 in  
Width: 35.59 in  
Height: 78.90 in  
Weight: 31.292 kg

## Electric

System power: 102 W  
Appliance Class: I

## Protection

IP: 20

## Adjustability

Free

## Design

Color of housing: White