

Product data sheet

LUCAS I (1-ARMED BEADED)
9.851.2032.16
LEIPZIGER LEUCHTEN



IP
55

Mounting heights between 4.00 - 6.00 m. - High-quality mirror optics to suit non-glare class KB1 - Aluminium cast luminaire body, inside white, outside painted in colour - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Luminaires with wiring ready for connection - Easy installation with adapter jack - Scope of supply includes complete unit with one/two painted special steel brackets - Available in any RAL or DB colour without surcharge - Pole for single-bracket luminaire: dia. 76 mm, please order separately inquire separately for pole to suit double-bracket luminaire, Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



1 x High pressure sodium vapour lamp

Nominal lamp power	70 W	LOR	83%
Lamp flux	5600 lm	ULOR	2%
Luminous efficacy	56 lm/W	Total flux	4642 lm
CCT	2000 K	Total power	83 W
CRI	25		

Mounting mode

Pole top mounted

Shape and measurements

Height: 19.69 in
Diameter: 22.44 in

Electric

System power: 83 W

Protection

IP: 55