Product data sheet


THIMBLE 70 TRIMLESS LED DE 3000K SPOT GOLD BRUSHED ANODISED
11622342
MODULAR



IP 55


Discrete, curvy & colourful Thimble evokes minimalism, surprise and technology all at once. Subtle curves, slightly revealing colours, high-quality lens and LED. With its deep-recessed and glare-free light source, Thimble's clean and seamless execution makes it a quiet yet sophisticated choice for high-end residential or hospitality settings. This versatile, elegant architectural downlighter will bring pure form, definition and quality light to any space without stealing all the attention.

Light output 1



1 x LED

Nominal lamp power	4.1 W	LOR	40%
Lamp flux	521 lm	Total flux	206 lm
Luminous efficacy	50 lm/W	Total power	4.1 W
CCT	3000 K		
CRI	90		



1 x LED

Nominal lamp power	6.1 W	LOR	40%
Lamp flux	704 lm	Total flux	279 lm
Luminous efficacy	46 lm/W	Total power	6.1 W
CCT	3000 K		
CRI	90		

Mounting mode

Ceiling recessed

Shape and measurements

Height: 3.35 in
Diameter: 2.91 in
Weight: 0.25 kg

Adjustability

Fixed

Electric

System power: 4.1-6.1 W

Protection

IP: 55