


# Product data sheet

BEAM ME UP SUSPENDED - P1  
MP10WE-840M-D400-UW  
LIGHTNET



LED pendant luminaire with a setback lens optic in a Décorative ring. Direct-indirect or direct-only light distribution. Luminaire body made of high-quality processed FRP (fiberglass reinforced plastic). Outer housing and Décorative reflector ring available in various finishes and combinations, e.g. white, silver, graphite, black, gold or copper coated. For surface options and combinations check Lightnet Surface Collection or Bi-Colour Selection. Microprismatic screen with optimized glare reduction especially for workplaces. Satin opal diffuser for general lighting with maximum transmittance and homogeneous lighting. Converter integrated into luminaire housing, optionally switchable or dimmable (1-10V, DALI, Touch-Dim, Casambi). Colour temperatures 2200K, 2700K, 3000K, 3500K, 4000K or 6500K. Binning initial  $\leq$  Mac Adam 3. Colour rendering CRI>80 or CRI>90. Height-adjustable parallel-cord suspension with transparent power supply cable.

## Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	20 W	CRI	82
Total flux	2230 lm	LOR	100%
Luminous efficacy	112 lm/W	ULOR	49%
		Total power	20 W

## Mounting mode

Pendant

## Electric

System power: 20 W

## Shape and measurements

Height: 15.75 in

Diameter: 15.75 in

## Protection

## Adjustability

Height adjustable