


# Product data sheet

INFINITE PRO 1136MM SUSPENDED HEXA-CELL


AK15-34W8HCD360

LEDSC4




LedsC4 Infinite Pro 1136mm Suspended Hexa-Cell AK15-34W8HCD360V3 Lineal lighting system for indoor use. For downlighting. Structure finish: Black. Diffuser material: Polycarbonate. Diffuser finish: Hexa-Cell. Warranty: 5 Years. Product net weight (Kg): 2.96 Product length (mm): 1136 Product width or diameter (mm): 52 Product height (mm): 90 Class 1. IP: IP20. LED. No. of lampholders or LEDs: 1. Driver brand: TCI. Maximum power of light source: 31.1W. Colour temperature: 3000K. Colour rendering index: 80. MacAdam Steps: 3. Hours of life: 80.000h L80B20. UGR: 10.8. Photobiological risk: RG1. % de Flickering: <5%. Real flux (lm): 1492. Real lm/W: 46. Voltage / frequency range: 220-240/50-60Hz. Voltage: 96. Equipment included: Yes. Total power: 32.6. Power factor: 0.95. Dimmable equipment included: DALI-2/PUSH.

## Light output 1 (emergency)



### 1 x LED

Nominal lamp power	3.8 W	LOR	100%
Lamp flux	65 lm	Total flux	65 lm
Luminous efficacy	17 lm/W	Total power	3.8 W
CCT	3000 K		
CRI	80		



### 1 x LED

Nominal lamp power	32.6 W	LOR	100%
Lamp flux	1492 lm	Total flux	1492 lm
Luminous efficacy	46 lm/W	Total power	32.6 W
CCT	3000 K		
CRI	80		

## Mounting mode

Ceiling mounted, Standing / Bollard

## Shape and measurements

Length: 2.05 in

Width: 44.72 in

Height: 3.54 in

## Adjustability

Fixed

## Electric

System power: 3.8-32.6 W

Appliance Class: I

## Information regarding emergency functions

Emergency lighting only

Emergency sign: N/A

## Protection

IP: 20