



# Product data sheet

LTUB60 SU RE 1120 1500 NW D/I COMF WH  
L61SE112LOIP940NW  
LAMP



Surface mounted luminaire Lamptub 60 from LAMP. Made of recycled aluminium extrusion with circular section of 60mm and length of 1120mm. Direct-indirect light model with opal comfort diffuser made of a translucent polycarbonate diffuser and an optical film to achieve a controlled light distribution and low glare level, less than UGR 19. Model for MID-POWER LED, with colour temperature 4000K with CRI 90. Built-in electronic ON/OFF control gear. With IP40, IK07 degree of protection. Insulation class I / II. Group 0 photobiological safety. Lifetime: 72.000h L80 B10. Compatible with Lamp Nomadic system. Available finishes: White (RAL 9010), Black (RAL 9011), Wellbeing and BeSocial palette.

## Light output 1



1 x LED			
Nominal lamp power	34.7 W	LOR	100%
Lamp flux	3089 lm	Total flux	3088 lm
Luminous efficacy	89 lm/W	Total power	34.7 W
CCT	3000 K		
CRI	90		

## Mounting mode

Pendant, Ceiling mounted

## Shape and measurements

Length: 68.03 in  
Width: 2.76 in  
Height: 2.56 in

## Adjustability

Fixed

## Design

Color of housing: Black, White

## Electric

System power: 34.7 W  
Appliance Class: I

## Protection

IP: 20  
IK: 07