


Product data sheet

GINEVRA
1113500
FLOS




• Outdoor/indoor floor lamp. • Configuration: vibrated and sandblasted concrete footing, extruded aluminium pole and white sanblasted polyethylene diffuser for a perfect light emission. • Double layer coating for high resistance to corrosion: The aluminium parts are painted with a double coat using powders which are complaint with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents).The entire painting process of the aluminium fitting starts from components which have been sand-blasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting.

Light output 1



1 x Halogen low voltage lamp without reflector

Nominal lamp power	100 W	Socket	E27
Lamp flux	1500 lm	LOR	94%
Luminous efficacy	40 lm/W	ULOR	48%
CCT	2800 K	Total flux	1407 lm
CRI	100	Total power	35 W



1 x Metal halide lamp

Nominal lamp power	35 W	Socket	G12
Lamp flux	3300 lm	LOR	94%
Luminous efficacy	88 lm/W	ULOR	48%
CCT	3000 K	Total flux	3096 lm
CRI	81	Total power	35 W

Mounting mode

Standing / Bollard, Floor mounted

Shape and measurements

Height: 23.62 in

Diameter: 19.69 in

Adjustability

Fixed

Electric

System power: 35 W

Appliance Class: I

Protection

IP: 65