


Product data sheet

MINI BUZZ2
7164-0-3-904-XX
UNILAMP



Description BUZZ is a robust ground mounted luminaire with excellent light control with 3 different types of light emission. BUZZ has a wide beam light distribution from a low mounting height and is the perfect fixture where foliage would normally cover an inground fixture. It is available in 2 sizes and operated with high power LED. It provides fantastic lighting level with no glare from the mounted view angle. With its robust aluminium construction and clear polycarbonate cover, it protects the luminaire from dust and water and possible harmful impact. BUZZ is generally installed in the walkways and pathways in both private and public areas. It provides visual guidance in the architectural environment as well as being an eye-catching object. Anchor unit for concrete foundation is available as an accessory. SPEC • Designed, Manufactured and Tested according to IEC 60598-1, IEC 60598-2-1 and VDE regulations. • LM6 Die Cast Aluminium body. • Stainless steel screws. • Nano Ceramic surface conversion. • Double layer coating. • Polycarbonate diffuser. • Post-cured silicone gasket. • High quality LED module and driver. • Anodized aluminium reflector • M20 cable gland. • Pre-wired with outdoor cable. • Gel-filled connection block. • Installation work has to be carried on according to the enclosed product manual.

Light output 1



1 x LED			
Nominal lamp power	12 W	LOR	88%
Lamp flux	1940 lm	Total flux	1704 lm
Luminous efficacy	162 lm/W	Total power	14 W
CCT	4000 K		
CRI	80		

Mounting mode

Standing / Bollard

Shape and measurements

Length: 6.74 in
Width: 6.74 in
Height: 5.71 in

Adjustability

Fixed

Electric

System power: 14 W
Appliance Class: I

Protection

IP: 67
IK: 07