# Product data sheet


QBA 1 70W 230V HIT-DE S/S
96012211
THORN LIGHTING



IP 66 IK 08

A compact discharge floodlight for architectural lighting with IP66 optical and gear compartment, SC1 class. Grey powder coated die-cast aluminium body with Flat Glass enclosure. Projector is fully adjustable on a short stirrup, locked via central 8mm diameter allen screws. symmetric floodlighting distribution with a aluminium - satinbrite reflector. This product is suitable for a 70 W HIT-DE-CE lamp. Available in other colours as special (any RAL number, brick brown or pale sand). Dimensions: 227 x 188 x 212 mm Weight: 5.4 kg

## Light output 1



### 1 x General service incandescent lamp

| | | | |
|---|---|---|---|
| Nominal lamp power | 70 W | LOR | 60% |
| Lamp flux | 6300 lm | Total flux | 3756 lm |
| Luminous efficacy | 44 lm/W | Total power | 85 W |
| CCT | 3000 K | | |
| CRI | 80 | | |

### Mounting mode

Ceiling mounted

### Shape and measurements

Length: 8.94 in
Width: 7.40 in
Height: 8.35 in
Weight: 5.4 kg

### Design

Material impression: Aluminum

### Electric

System power: 85 W
Voltage: 230-240 V AC
Appliance Class: I

### Protection

IP: 66
IK: 08
Designation labels: CE