Product data sheet


ROAD [5] MEDIUM 5X3 LED WIDE 155W 740 GR-RAL9006 RPA
GWR5715B
PERFORMANCE IN LIGHTING



IP 66 IK 08

Part number: GWR5715B. Serie: Road [5]. Street lighting device with cover, frame, and pole attachment in EN AB 46100 die-cast aluminium with low copper content: Polyester powder coated. High-power LED. Printed Circuit Board (PCB) in metal core. Common mode surge protection up to 10kV. With safety switch. Cable plate in PA6.6 + glass fiber. Cable input via PG13.5 cable gland. High reflective aluminium optical system. Tempered flat glass with 4 mm thickness. Opening and closing system with integrated front handle. It can be used up to 50°C of ambient temperature but with reduced currents as indicated in the instruction manual. Suitable for installation both on top of the pole and offset with 5° pitch adjustment. L90B10 (Tq 25°C) 115.000 h; L90B10 (Tq 40°C) = 115.000 h. Product data | ETIM Group: EG000027. ETIM Class: EC000062. General information | Lampholder: LED. Luminaire lumen output [lm]: 21500. Luminaire wattage [W]: 155 W. Luminous efficacy [lm/W]: 139. CRI: 70. Colour temperature [K]: 4000. Colour / Finishing: GR-RAL9006 / Grey RAL9006. IP degree of protection: IP66. IK08 5J xx5. Protection class: I. Optic: WIDE - Street. Net weight [kg]: 9.365. Overall length [mm]: 690. Overall width [mm]: 330. Overall height [mm]: 215. Mechanical features | Housing material: Aluminium. Diffuser material: Glass. Electrical features | Voltage type: AC. Input voltage [V AC]: 220/240. Input frequency [Hz]: 50/60. Surge protection | Differential [kV]: 10.000000. Automatic power reductor. Installation | Application area: PROFESSIONAL OUTDOOR. Mounting type: Street lighting. Min. ambient temperature [°C]: -25. Max. ambient temperature [°C]: 40. Light features | MacAdam: 5. Lumen maintenance: L90B10@115000h. Distribution of light emission: Direct. Luminous Intensity Class: G*4. IPEA* (road lighting): A4+. IPEA* (large areas, roundabouts): A7+. IPEA* (cycle-pedestrian): A4+. IPEA* (green areas): A5+. IPEA* (historic city centers): A12+. Certifications | CE certified. UKCA certified.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	155 W	CRI	70
Total flux	21500 lm	LOR	100%
Luminous efficacy	139 lm/W	Total power	155 W

Mounting mode

Pole top mounted

Shape and measurements

Length: 3.54 in
Width: 3.54 in
Height: 7.91 in

Adjustability

Tiltable

Electric

System power: 155 W
Appliance Class: 0

Protection

IP: 66
IK: 08
Designation labels: CE

Design

Color of housing: Silver gray