Product data sheet


ABRB-R2X115/30DA-SM-300M840
0660329
RIDI



IP 20

Surface mounted luminaire ABRB-R Design: Surface mounted ceiling luminaire, suitable for continuous mounting. For continuous mounting, a louvre with continuous optical effect is used. Luminaire housing in sheet steel, white powder coated, colour similar to RAL 9016. Luminaire end pieces and luminaire joining pieces made of UV-resistant plastic must be ordered separately, see Accessories. The louvre hinges down on both sides and is independently earthed for electrical safety Electronic DALI converter for LED, 230 Volt, 0/50-60 Hz and internal connector block. Suitable for direct voltage operation and use in central battery systems. Mounting: Single and continuous luminaire mounting using a simple toolless quick-mounting system for substantially reduced installation time. Fixing clips create a distance of 5 mm between the ceiling and luminaire. Electrical connection from the outside at the top of the luminaire, which is recessed to accommodate the connecting cable and through wiring. ABRB-R ... SM Parabolic mirror louvre SM, constructed of high-reflectance silk matt, super-purity anodised aluminium with silver coating

Light output 1



2 x LED

Nominal lamp power	21 W	LOR	79%
Lamp flux	3020 lm	ULOR	4%
Luminous efficacy	114 lm/W	Total flux	4794 lm
CCT	4000 K	Total power	42 W
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 46.46 in
Width: 8.46 in
Height: 2.36 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 42 W
Appliance Class: I

Protection

IP: 20