Product data sheet

LUXCAN MICRO SUSPENDED SEMI-RECESSED 600 36° EDD 04 930 / S-1,5M
19.4375.1333.04
LUXIONA



IP 20 IK 04

Indoor luminaire. Assembly: on slings from the suspended ceiling. The body material is aluminum. Colour - RAL 9005 (black). Dimensions: Ø33 x 65 mm. Diffuser: optical system based on PMMA lenses. The efficiency of the optical system is 79,88%. Beam angle: (C0-C180) / (C90-C270) - 34° / 38,2°. Light source type: LED. Colour of the light 3000 K. SDCM=3. CRI>90. Lifetime of LED sources: 100000 h L80/B10. Luminaire luminous flux: 448,7 lm. Power of luminaire: 5,4 W. Luminaire's light efficiency: 83,1 lm/W. Driver: DIM DALI (EDD). Voltage 220..240 V, 50..60 Hz. Power factor cosφ: >0,95. Operating temperature range: 5 ÷ 35° C. Protection degree: IP20. Impact resistant: IK04. Protection against electric shock: III. Photobiological risk class (IEC/EN 62471): RG0.

Light output 1



1 x LED

Nominal lamp power	5.4 W	LOR	52%
Lamp flux	562 lm	Total flux	295 lm
Luminous efficacy	104 lm/W	Total power	5.4 W
CCT	3000 K		
CRI	90		

Mounting mode

Pendant

Shape and measurements

Height: 2.56 in
Diameter: 1.30 in

Adjustability

Fixed

Design

Color of housing: Black

Electric

System power: 5.4 W
Controller: DALI
Appliance Class: III

Protection

IP: 20
IK: 04

Other operating numbers

Ambient temperature range: 41...95°F