Product data sheet


FLEX50
FX50A-B98401-LXXXM
EGLO



IP 20


surface mounted direct LED luminaire;

Light output 1 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	1.55 W	CRI	80
Total flux	189 lm	LOR	100%
Luminous efficacy	122 lm/W	ULOR	71%
		Total power	1.55 W

Light output 2 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	1.55 W	CRI	80
Total flux	189 lm	LOR	100%
Luminous efficacy	122 lm/W	ULOR	71%
		Total power	1.55 W

Light output 3 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	1.55 W	CRI	80
Total flux	189 lm	LOR	100%
Luminous efficacy	122 lm/W	ULOR	71%
		Total power	1.55 W

Light output 4 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	1.55 W	CRI	80
Total flux	189 lm	LOR	100%
Luminous efficacy	122 lm/W	ULOR	71%
		Total power	1.55 W

Light output 5 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	1.55 W	CRI	80
Total flux	189 lm	LOR	100%
Luminous efficacy	122 lm/W	ULOR	71%
		Total power	1.55 W

Light output 6 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	1.55 W	CRI	80
Total flux	189 lm	LOR	100%
Luminous efficacy	122 lm/W	ULOR	71%
		Total power	1.55 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 22.09 in

Width: 22.09 in

Height: 3.15 in

Adjustability

Fixed

Electric

System power: 9.28 W

Protection

IP: 20

Designation labels: CE