
Product data sheet


FLEXLINE - 36 W - 7.5 W/M - METALLISED REFLECTOR - CORNER 2.4 M
FL36C24M
THORLUX LIGHTING



IP 20

Extremely narrow-profile linear luminaires. A super-narrow linear luminaire designed for mounting to exposed T-bar ceilings. With sophisticated, high-efficiency, low-glare optics, Flexline offers a radically different alternative to conventional 600 x 600 luminaires. Designed for use either independently or paired with the Flexview "picture window" luminaire, Flexline provides the lighting designer with a wide range of aesthetic options. Furthermore, this updated version offers a range of 600 x 600 squares to match the spacing arrangements of flat panel luminaires. Applications: teaching spaces, offices, meeting rooms, corridors, waiting rooms, break-out spaces, reception areas, and retail.


Light output 1



1 x LED

Nominal lamp power	18 W	LOR	100%
Lamp flux	3315 lm	Total flux	3315 lm
Luminous efficacy	184 lm/W	Total power	21 W
CCT	4000 K		
CRI	80		

Light output 2



1 x LED

Nominal lamp power	18 W	LOR	100%
Lamp flux	3315 lm	Total flux	3315 lm
Luminous efficacy	184 lm/W	Total power	21 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 94.49 in
Width: 0.94 in
Height: 0.94 in

Adjustability

Fixed

Electric

System power: 42 W

Protection

IP: 20